


Genset Model:

# YIV105RSC Rental

Enclosed set



Socket Panel Option



Frequency	Phases	Power Factor	Prime Output	Standby Output
50Hz	3	0.8	105 kVA / 84 kW	115 kVA / 92 kW

## Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity

## Design features

- High quality assembly, providing stiffness and low vibration
- Power coated steel. Corrosion and scratch resistant.
- Compact and long service life
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month warranty

## Design Standards

- CE marking
- ISO8528-1995
- GB/T2820-1997
- ISO 9001:2008 Registered Company

## Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Coolant recovery tank
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings
- Integral 24 hour fuel tank with fully bunded base protection.
- Fuel level sensor
- Auto start control system with electronic digital control module DSE6010MKII
- Output circuit breaker.
- Emergency stop button
- High engine temperature and low oil pressure shutdown system.
- 12V starter battery with leads and switch

## Acoustic canopy features

- Water and dust proof design
- Door locks
- High quality sound absorbing and fire retardant inner material
- Lifting lugs
- Forklift holes in base

\*\* The images above are for illustration purposes only.




## Engine data

Engine brand	Volvo	Total oil consumption	0.11 %
Engine model	TAD551GE (IIIA)	Total lube oil capacity	21.00 Litres
Engine speed	1500 RPM	Cooling air flow	5040 m³/h
Number of cylinders	4	Exhaust gas flow	1248 m³/h
Aspiration	Natural	Exhaust gas temperature	530 °C
Combustion system	Direct injection		
Displacement	3.3 Litres	Fuel cons. @ 100% Prime load	26.10 l/hr
Governor type	Electronic	Fuel cons. @ 75% Prime load	21.70 l/hr
Cooling system	Water Cooled	Fuel cons. @ 50% Prime load	15.20 l/hr

## Alternator data

Alternator brand	Meccalte	Number of wires	12 re-connectable
Alternator model	ECP34-2S/4	No. Poles	4
Excitation	Self excited	Voltage regulator	DSR
Insulation class	H	Efficiency Alt 3/4 %	92.50
Drip proof protection	IP23	Efficiency Alt 4/4 %	92.20
Winding pitch	2/3 (wdg 6)	Flanges and shield	Aluminium

## Enclosed set data



L x W x H (mm)	Weight	Fuel tank	Noise@7M
2990 x 1140 x 1900	2170Kgs	480 Litres	68dBA

\*\* Due to constant innovation, design and specifications are subject to change without notice.

**Tel: +44 (0) 1977 688155**  
**Fax: +44 (0) 1977 688158**

