




YORPOWER



RATING	MODEL	ENGINE
16kVA Canopied Set	YXP16D6S	

GENERAL	
OUTPUT RATINGS 60Hz,	
Prime	16kVA, 13kW
Standby	18kVA, 14kW
ENGINE	PERKINS 403D-15G
ALTERNATOR	LEROY SOMER



TECHNICAL DATA			
Engine Model	403D-15G	Engine Speed	1800RPM
Cylinders	3	Fuel Cons: 100% Load (l/hr)	4.4
Displacement	1.496 Litres	Fuel Cons: 75% Load (l/hr)	3.4
Coolant Capacity	6.0 Litres	Oil Capacity	6.0 Litres
Cooling	Water Cooled	DBA @ 7M	56.6
Fuel Tank Capacity	90 Litres	Intake System	Natural aspirated

These ratings are suitable for Prime Continuous power output at varying load with no limitation on annual hours of operation.
The Generator will supply 10% overload for 1 in 12 hours.

GENERAL ARRANGEMENT	
	

DIMENSIONS AND WEIGHTS			
Length mm	Width mm	Height Mm	Weight Kg
1632	874	1225	695

We reserve the right to amend specifications without notice. All ratings are at standard ISO conditions
Alternators may vary subject to lead time and availability

Registered Office:
Yorpower Limited
Unit 2, Hurricane Close
Sherburn In Elmet
LS25 6PB
UNITED KINGDOM



T: +44 (0) 1977 688155
F: +44 (0) 1977 688158
E: sales@yorpower.com
W: www.yorpower.com

Yorpower Limited, Registered in England and Wales No. 7035780