



Genset Model:

**PG13RSC**

Enclosed set



Open set



Frequency

Phases

Power Factor

Prime Output

Standby Output

50Hz

3

0.8

13 kVA / 10 kW

14 kVA / 11 kW

### Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity

### Design features

- High quality assembly, providing stiffness and low vibration
- Power coated steel. Corrosion and scratch resistant.
- Compact and long service life
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month YorPower warranty

### Design Standards

- CE marking
- ISO8528-1995
- GB/T2820-1997
- ISO 9001:2008 Registered Company

### Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Coolant recovery tank
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings
- Integral fuel tank with fully banded base protection.
- Fuel level sensor
- Auto start control system with electronic digital control module DSE7420
- Output circuit breaker.
- Emergency stop button
- High engine temperature and low oil pressure shutdown system.
- 12V starter battery with leads and switch

### Acoustic canopy features

- Water and dust proof design
- Door locks
- High quality sound absorbing and fire retardant inner material
- Lifting lugs
- Forklift holes in base

\*\* The images above are for illustration purposes only.



## Engine data

Engine brand	Perkins	Total coolant capacity	6.0 Litres
Engine model	403D-15G	Total lube oil capacity	6.0 Litres
Engine speed	1500 RPM	Cooling air flow	TBC
Number of cylinders	3	Exhaust gas flow	2.9 m <sup>3</sup> /min
Aspiration	Natural	Exhaust gas temperature	490°C
Combustion system	Indirect injection	Fuel cons. @ 110% standby load	4.0 l/hr
Displacement	1.496 Litres	Fuel cons. @ 100% Prime load	3.6 l/hr
Governor type	Mechanical	Fuel cons. @ 75% Prime load	2.8 l/hr
Cooling system	Water Cooled	Fuel cons. @ 50% Prime load	2.0 l/hr

## Alternator data



Alternator brand	Leroy Somer	Number of wires	12 re-connectable
Alternator model	LSA40.VS2	AVR model	R 220
Excitation	Self excited	Voltage regulation	± 0.5%
Insulation class	H	Total Harmonic distortion	No load < 3%, on load < 2%
Drip proof protection	IP23	Telephone interference	TIF < 50%
Winding pitch	2/3 (wdg 6)	Flanges and shield	Aluminium

## Enclosed set data



L x W x H (mm)	Weight	Fuel tank	Noise@7M
1940 x 910 x 1227	TBC	TBC	64 db

## Open set data



L x W x H (mm)	Weight	Fuel tank	Noise@7M
1439 x 600 x 1118	495 kg	80 Litres	95db

\*\* Due to constant innovation, design and specifications are subject to change without notice.